PRODUCT BULLETIN

TCC-1479

LACQUER SANDING SEALER

TOOL CHEMICAL COMPOSITES

www.CASSpolymers.com **800.344.7776** **TCC@CASSpolymers.com**
31200 Stephenson Hwy **Madison Heights MI 48071** **Ph 248.588.2270 Fax 248.588.5909**

DESCRIPTION

Lacquer Sanding Sealer TCC-1479 provides a rapid drying seal for plaster and wood. It is also an excellent sealer for MP-1055 Model Plank®, FP-1050 Fixture Plank®, and DP-1051 Die Plank®. This material is easily sandable and provides a smooth, sealed surface. One or more coats may be used, applied to a clean and dust free substrate. These coats are dry and sandable at the following rates:

FILM THICKNESS	TAC FREE	SANDABLE
.005	6 minutes	8 - 10 minutes
.010	10 minutes	1 hour

PHYSICAL PROPERTIES

Density (7.5 lb gallon) 0.9
*Viscosity ..... 140 cps
Optimum Coverage (1 mil dry) ..... 262 ft^2/gal
Shelf Life (in original unopened containers) ..... 2 years

*May be thinned with Lacquer Thinner.

SANITARY PRECAUTIONS

Do not take internally. Avoid prolonged breathing of vapors. Work in a well-ventilated area. Avoid skin contact. Protective gloves should be worn. If contact occurs: wash skin with soap and water. Avoid eye contact. If contact occurs: rinse well with water for 15 minutes, contact physician.

STORAGE AND HANDLING

Stir well before use. FLAMMABLE MATERIAL. Store in a dry area at room temperature. Avoid extreme temperatures and elongated storage times.

TCC-1479 Tech/Revised 5/20/10
Supercedes 6/20/06

Seller cannot anticipate all conditions under which seller's products, or the products of other manufacturers in combination with seller's products, may be used. Seller accepts no responsibility for results obtained by the application of seller's products or the safety and suitability of seller's products, either alone or in combination with other products. Users are advised to make their own test to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, seller delivers the products without warranty of any nature, stated or implied, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of said products, whether used alone or in combination with other products. Purchaser waives any claim against seller for direct, indirect, consequential or exemplary damages against seller, including without limitation, damage which may incur as a result of purchaser's use or misuse of the product or the products failure to conform to any particular specifications.